



*Binocular microscope, 600x,
achromatic objectives*

Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	As optional
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Transportation handle	Yes
Head	Type	Binocular (Siedentopf)
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	55-75
	Diopter adjustment	On left tube
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-600x
	Type	Achromatic
		4x/0.10, W.D. 10.6 mm
		10x/0.25, W.D. 7.0 mm
		40x/0.65, W.D. 0.5 mm
	60x/0.85, W.D. 0.13 mm	

Stage	Type	Double layer
	Dimensions (mm)	125x125
	Moving mechanism	Rack and pinion
	Moving range (mm)	62x24
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
Condenser - Single Position	Type	Abbe
	Numerical aperture (N.A.)	1.25
	Diaphragm	Iris
	Focusable	By rotation
Focusing System	Type	Coaxial coarse & fine
	Coarse total travel (mm)	23
	Fine total travel (per single rotation) (mm)	1,2
	Fine graduations	100
	Fine resolution (µm)	12
Upper stop to prevent contact	Yes	
Transmitted Illumination	Type	LED
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
Max. required power (W)	1,5	
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 2,5A
	Use with batteries	Yes, not supplied
	Battery type	Ni-MH (3x, AAA size), 1.2V, 650mAh
	Working time of batteries (hours)	up to 8
Charging time of batteries (hours)	8	
Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)
Product Dimensions	Height (mm)	330
	Width (mm)	135
	Depth (mm)	235
Product Weight	(kg)	2,9