Binocular phase contrast microscope, 1000x, IOS W-PLAN PH objectives, with Automatic Light Control

Main Body	Type	Upright
	Construction material	Aluminum die-cast
	with trasportation handle	Yes
	Internal prism	Glass prism
	Optical system	Infinity
	Optics with anti-fungus treatment	Yes

Head (*) with limitations	Type	Binocular
	Construction	Siedentopf
	Inclination	30°
	Rotation	360°(*)
	Fixing screw for eyepieces	Yes
	Diopter adjustment	On left tube
	Diopter compensation	±5
	Interpupillary distance (mm)	48-75
	Tube inner diameter (mm)	23

Eyepieces	Magnification	10x
	Field number (mm)	20
	High eyepoint (for glass wearers)	Yes
	Micrometric scale	Optional
	Diameter of micrometer glass (mm)	21
	Rubber cup	Yes

Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Type	IOS W-PLAN PH
	Correction	Plan Achromatic
	Parfocal distance (mm)	DIN 45
	Optical system	Infinity
	Standard magnifications	10x-20x-40x-100x
		M-1120.N
		M-1121.N
		M-1122.N
		M-1123.N

Stage	Dimensions (mm)	233x147
	Mechanical stage	Rackless
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	2
	Moving range (mm)	78x54
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
	Type	Double layer
	Right / Left hand	Right

Condenser - Multiple Position	Type	Abbe. Brightfield - Phase Contrast - Darkfield (dry)
	Number of positions	5 (BF, 10x/20x, 40x, 100x, DF)
	Numerical aperture (N.A.)	0.9 / 1.25
	Aperture diaphragm	Iris
	Removable	Yes
	Centerable	Yes
	Focusable	By rack and pinion

Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	25
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0,2
	Fine resolution (µm)	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomy	Yes

Observation Method - Transmitted Light	Brightfield	Yes
	Phase contrast (Positive type)	Yes
	Darkfield	Yes
	Simple polarized light	Optional

Transmitted Illumination	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual & Automatic (ALC)
	Kohler illumination	Fixed (full Optional)
	Color Temperature (K)	5,500-5,700
	Lifetime (hours)	> 65,000
	Max. required power (W)	6

Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 2,5 A

Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	Allen wrench	Yes
	Centering telescope	Yes
	Green filter	Yes
	LBD filter	No
	Spare halogen lamp	No
	User Manual	Digital version (downloadable)

Product Dimensions (footprint)	Width (mm)	245
	Depth (mm)	210

Product Dimensions (overall footprint)	Height (mm)	405
	Width (mm)	245
	Depth (mm)	370

Product Weight	(kg)	7,8