



*Trinocular HBO fluorescence microscope,
1000x,
IOS N-PLAN objectives,
Blue & Green filtersets*

Main Body	Type	Upright
	Construction material	Aluminum die-cast
	with transportation handle	Yes
	Internal prism	Glass prism
	Optical system	Infinity
	Optics with anti-fungus treatment	Yes

Head (*) with limitations	Type	Trinocular
	Construction	Siedentopf
	Inclination	30°
	Rotation	360°
	Fixing screw for eyepieces	Yes
	Diopter adjustment	On left tube
	Diopter compensation	+5
	Interpupillary distance (mm)	48-75
	Split ratio	50/50
	Tube inner diameter (mm)	23

Eyepieces	Magnification	10x
	Field number (mm)	20
	High eyepoint (for glass wearers)	Yes
	Micrometric scale	Optional
	Diameter of micrometer glass (mm)	21
	Rubber cup	Yes

Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Type	IOS N-PLAN
	Correction	Plan Achromatic
	Parfocal distance (mm)	DIN 45
	Optical system	Infinity
	Standard magnifications	4x-10x-40x-100x
		M-164
		M-165
	M-167	

		M-169
Stage	Dimensions (mm)	233x147
	Mechanical stage	Rackless
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	2
	Moving range (mm)	78x54
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
	Type	Double layer
	Right / Left hand	Right
Condenser - Single Position	Type	Abbe
	Numerical aperture (N.A.)	0.9 / 1.25
	Magnification scale for simplified positioning	Yes
	Aperture diaphragm	Iris
	Removable	Yes
	Slot for sliders	Yes
	Slider for phase contrast	Optional
	Slider for darkfield (dry)	Optional
	Centerable	Yes
	Focusable	By rack and pinion
Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	25
	Fine graduations	190
	Fine total travel (per single rotation) (mm)	0,2
	Fine resolution (μm)	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomoy	Yes
Observation Method - Transmitted Light	Brightfield	Yes
	Phase contrast (Positive type)	Optional
	Darkfield	Optional
	Simple polarized light	Optional
Observation Method – Reflected Light	Fluorescence	Yes
Transmitted Illumination	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Kohler illumination	Fixed (full Optional)
	Color Temperature (K)	6,300
	Lifetime (hours)	> 65,000
	Max. required power (W)	6
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5V 2.5A

Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	Allen wrench	Yes
	User Manual	Digital version (downloadable)
Product Dimensions (footprint)	Width (mm) (E)	245
	Depth (mm) (D)	210
Product Dimensions (overall footprint)	Height (mm) (C)	485
	Width (mm) (B)	245
	Depth (mm) (A)	530
Product Weight	(kg)	12.4 (including FLUO power supply)
Fluorescence Attachment	Number of positions	3
	Number of fluorescence cubes available	2
	Filter dimensions	Excitation: 25 mm diam.; Dichroic: 36 mm x 25 mm; Emission: 25 mm diam.
	Blue filter set (included)	Excitation: 460 - 495 nm; Dichroic: 505 nm; Emission: 510LP nm
	Green filter set (included)	Excitation: 510 - 550 nm; Dichroic: 570 nm; Emission: 575LP nm
	Filter set selection	Manual
	LED source insertion	Manual
	Shutter	Yes
Fluorescence Light Source	Light source	HBO
	Light source power (W)	100
	Lifetime (hours)	200
Fluorescence Power Supply	Type	External
	Microscope connector	C13 plug
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	110/240 Vac, 50/60 Hz
	Max. power required (W) / Output voltage	130
	LED indicators	Yes