



*Digital video microscope, 400x,
HC objectives*

Main Body	Type	Upright
	Construction material	Aluminum die-cast
	with transportation handle	Yes
	Internal prism	Glass prism
	Optical system	Finite 160 mm
	Optics with anti-fungus treatment	Yes
Head	Type	Monocular
	Inclination	30°
	Rotation	360°
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Magnification	10x
	Field number (mm)	18
	High eyepoint (for glass wearers)	Yes
	Micrometric scale	Optional
	Diameter of micrometer glass (mm)	20
Nosepiece	Positions	Quadruple
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Type	HC
	Correction	Achromatic
	Parfocal distance (mm)	DIN 45
	Optical system	Finite 160 mm
	Standard magnifications	4x-10x-40x
		M-137
		M-138
		M-141

Stage	Dimensions (mm)	130x120
	Mechanical stage	Optional
	Material	Anti-scratch painting
	Specimen clips	Yes
	Slide number	1
	Type	Fixed
Condenser - Single Position	Type	Fixed
	Numerical aperture (N.A.)	0.65
	Aperture diaphragm	Iris
	Holder for color filters	Yes
	Centerable	Pre-centered
Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	16
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0,4
	Fine resolution (μm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	Optional
Transmitted Illumination	Type	X-LED
	X-LED type	X-LED1
	Light source power (W)	1
	Brightness control	Manual
	Color Temperature (K)	6,300
	Lifetime (hours)	> 65,000
	Max. required power (W)	1,5
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 2,5 A
Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	Green filter	Yes
	User Manual	Digital version (downloadable)
Product Dimensions (footprint)	Width (mm)	145
	Depth (mm)	220
Product Dimensions (overall footprint)	Height (mm)	385
	Width (mm)	175
	Depth (mm)	275
Product Weight	(kg)	4,3

Camera General specifications	SD Card Still image capture	Yes
	SD Card Video recording	Yes
	Height (mm)	150
	Width (mm)	180
	Depth (mm)	90
	Weight (kg)	0.360
Sensor	Camera resolution (n° of pixels: W x H)	1844x1080
	Color / Monochrome	Color
	Sensor Size	1/2.8"
	Sensor Technology	CMOS
	Sensor Type	MICRON CMOS
	Image Format	16:9
	Pixel Size (mm)	2.9x2.9
	Acquisition technology	Rolling shutter
	Exposure time	0-33333ms
	IR filter	Yes
IR filter range (nm)	680	
USB	Camera resolution (MP)	2
	Frame rate full resolution (fps)	30@1844x1080
Camera Power Supply	Type	External
	Connector	Jack, 2.1 mm
	Power plug type	Multiplug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60Hz
	Output voltage	5V 2,5A
	LED indicator	Yes
Available Software	Built-in Camera SW	S-Viewer
HDMI Monitor	Display size	7"
	Display resolution	1024x600
System accessories	SD card	4GB
	USB SD card reader	Yes
General	Built-in SW Specifications	
	Multi-language menu	Yes
	Available languages	
	Catalan	No
	Chinese	Yes
	English	Yes
Russian	Yes	
Image Acquisition	Continuous automatic exposure	Yes
	Manual exposure	Yes
	Color acquisition	Yes
	Gray-scale acquisition	Yes
	Manual Time-lapse	Yes
	White Balance	Auto/Manual
	Image enhancement	Yes
	Horizontal Flip	Yes
	Verical Flip	Yes
Image Processing	Grids	Yes

Measurements	Still image measurement	Yes
	Select measurement unit	Yes
	Available measurements	
	Line	Yes