



*Trinocular LED fluorescence microscope,
500x, IOS objectives, blue filterset*

Observation Method - Transmitted Light	Brightfield	Yes
	Phase contrast (Positive type)	As optional
	Darkfield	As optional
	Simple polarized light	As optional
Observation Method - Incident Light	Fluorescence	Yes
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Transportation handle	Yes
Head	Type	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	55-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
Eyepieces	Tube inner diameter (mm)	23
	Field number (mm)	20
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	21
	High eyepoint (for glass wearers)	Yes
Nosepiece	Rubber cup	Yes
	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Optical system	∞
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	100x-500x
	Type	IOS
		IOS N-PLAN 10x/0.25, W.D. 5.8 mm
		IOS N-PLAN 20x/0.40, W.D. 5.1 mm
		IOS N-PLAN 40x/0.65, W.D. 0.43 mm
		IOS W-PLAN MET 50x/0.75, W.D. 0.32 mm

Stage	Type	Double layer
	Dimensions (mm)	150x140
	Moving mechanism	Rackless
	Moving range (mm)	75x33
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1

Condenser - Single Position	Type	Abbe
	Removable	Yes
	Numerical aperture (N.A.)	1.25
	Magnification scale for simplified positioning	Yes
	Diaphragm	Iris
	Centrable	Yes
	Focusable	By rack and pinion

Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	18
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0,4
	Fine resolution (μm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes

Transmitted Illumination	Kohler illumination	Fixed
	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	6

Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	6 Vdc 2.5 A

Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes

	User Manual	Digital version (downloadable)
Additional Information		Mirror for transmitted light (as optional). External rechargeable battery pack (as optional).
Product Dimensions	Height (mm)	515
	Width (mm)	235
	Depth (mm)	340
Product Weight	(kg)	7.5
Fluorescence Attachment	Number of positions	3
	Blue filter set (included)	Excitation: 460 - 495 nm; Dichroic: 505 nm; Emission: 510LP nm
	Filter dimensions	Excitation: 18 mm diam.; Dichroic: 26.5 mm x 19 mm; Emission: 18 mm diam.
	Filter set selection	Manual
Fluorescence Light Source		Blue LED
	Light source power (W)	3.6
	LED wavelength	Blue LED: 465 nm
	Lifetime (hours)	> 65,000
	Brightness control	Yes