

Trinocular discussion microscope,
2-head (face-to-face), 1000x,
IOS W-PLAN objectives

Main Body	Type	Upright
	Construction material	Aluminum die-cast
	with trasportation handle	Yes
	Internal prism	Glass prism
	Optical system	Infinity
	Optics with anti-fungus treatment	Yes

Head	Type	Trinocular
	Construction	Siedentopf
	Inclination	30°
	Rotation	360°
	Diopter adjustment	On left tube
	Diopter compensation	±5
	Interpupillary distance (mm)	50-75
	Split ratio	50/50
	Tube inner diameter (mm)	30

Eyepieces	Magnification	10x
	Field number (mm)	22
	High eyepoint (for glass wearers)	Yes
	Planar type	Yes
	Micrometric scale	Optional
	Diameter of micrometer glass (mm)	26
	Rubber cup	Yes
	Retractable protections	Yes

Additional Eyepieces	Magnification	10x
	Field number (mm)	20
	High eyepoint (for glass wearers)	Yes
	Planar type	Yes

Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Type	IOS W-PLAN
	Correction	Plan Achromatic
	Parfocal distance (mm)	DIN 45
	Optical system	Infinity
	Standard magnifications	4x-10x-40x-100x
Stage	Dimensions (mm)	233x147
	Mechanical stage	Rackless
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	2
	Moving range (mm)	78x54
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
	Type	Double layer
	Right / Left hand	Right
Condenser - Single Position	Type	Swing-out
	Numerical aperture (N.A.)	0.2 / 0.9
	Numerical aperture scale	Yes
	Aperture diaphragm	Iris
	Removable	Yes
	Centerable	Yes
	Focusable	By rack and pinion
Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	25
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0,2
	Fine resolution (µm)	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomy	Yes
Observation Method - Transmitted Light	Brightfield	Yes
	Phase contrast (Positive type)	Optional
	Darkfield	Optional
	Simple polarized light	Optional
Transmitted Illumination	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Kohler illumination	Full
	Color Temperature (K)	5,500-5,700
	Lifetime (hours)	> 65,000
	Max. required power (W)	6
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5Vdc 2.5 A

Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	Allen wrench	Yes
	User Manual	Digital version (downloadable)
Product Dimensions (footprint)	Width (mm)	250
	Depth (mm)	260
Product Dimensions (overall footprint)	Height (mm)	490
	Width (mm)	270
	Depth (mm)	660
Product Weight	(kg)	12
Discussion Heads for Multi-Head Attachment	Type	Binocular (Siedentopf)
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Diopter adjustment	On both tubes
	Inner diameter (mm)	30
Eyepieces for Multi-Head Attachment	Field number (mm)	20
	Magnification	10x
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
	Retractable protections	No
Pointer for Multi-Head Attachment	Multi color pointer	Yes
	Color of the pointer	Red-Green-Blue
	Light source	RGB LED
	Brightness control	Yes
	360° rotating	Yes
	Power supply type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA