



USB 2.0 C-mount and Eyepiece Microscope Camera

General specifications	USB output	Yes
	C-Mount	Yes
	Dimensions (mm)	58 x 58 x 36.4
	Weight (kg)	0.18
Sensor	Camera resolution (n° of pixels: W x H)	4632x3488
	Color / Monochrome	Color
	Sensor Size	1/2.3"
	Sensor Technology	CMOS
	Sensor Type	APTINA CMOS
	Image Format	4/3
	Pixel Size (µm)	1.335x1.335
	Acquisition technology	Rolling shutter
	Dynamic range (DB)	65
	ADC conversion	8 Bit
	Color Depth	1, 4, 8, 24 Bit
	Exposure time	0.2 msec - 2 sec
	Binning	1x1; 2x2; 3x3
	IR filter	Yes
IR filter range (nm)	380-650 (IR CUT)	
USB	PC Camera resolution (MP)	16
	USB standard	USB2.0
	Frame rate full resolution (fps)	2@4632x3488
	Frame rate other resolution (fps)	8@2320x1740; 11@1536x1160
Camera Power Supply	Connector	USB
	Output voltage	PC USB
Camera accessories	Optical adapter (for 23mm eyepiece tube)	0.5x
	Adapter ring	Yes
	Diameter of adapter ring (mm)	30
	Diameter of adapter ring (mm)	30.5
	Calibration slide	Yes
	USB cable (1.8m)	Yes

Environment	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%
Operating System	OS	Windows 7
	OS	Windows 8
	OS	Windows 10 (32Bit)
	OS	Windows 10 (64Bit)
	OS	Osx (MAC Osx) starting from 10.7.5
	OS	Linux
Available Software	PC SW	PROVIEW
	PC SW	LITEVIEW
PC requirements	PC	CPU: Intel Core2 - 2.8GHz or higher
	PC	RAM: 2GB or more
	PC	USB 2.0