

4-position LED Fluorescence attachment (without LED Fluorescence Cube)

Main Body	Туре	Upright
•	Construction material	Aluminum die-cast / Plastic
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Allen wrench	Yes
	User Manual	Yes
Product Dimensions	Height (mm)	55
	Width (mm)	276
	Depth (mm)	222
Product Weight	(kg)	2,5
Fluorescence Attachment	Number of LED Cubes	Up to 4
		LED Emission: 460 nm.
	BLUE LED Cube (Optional)	Excitation: 455 - 495 nm;
		Dichroic: 500 nm;
		Emission: 510LP nm
	BLUE BANDPASS LED Cube (Optional)	LED Emission: 460 nm.
		Excitation: 455 - 495 nm;
		Dichroic: 500 nm;
		Emission: 518-542 nm
	GREEN LED Cube (Optional)	LED Emission: 523 nm.
		Excitation: 510 - 550 nm;
		Dichroic: 570 nm;
		Emission: 575LP nm
	GREEN BANDPASS LED Cube (Optional)	LED Emission: 523 nm.
		Excitation: 510 - 550 nm;
		Dichroic: 570 nm;
		Emission: 585-625 nm
	UV LED Cube (Optional)	LED Emission: 365 nm.
		Excitation: 325 - 375 nm;
		Dichroic: 415 nm;
		Emission: 435LP nm
	UV BANDPASS LED Cube (Optional)	LED Emission: 365 nm.
		Excitation: 340 - 390 nm;
		Dichroic: 405 nm;
		Emission: 420-470 nm
	V LED Cube (Optional)	LED Emission: 405 nm.
		Excitation: 390 - 420 nm;
		Dichroic: 440 nm;
		Emission: 450LP nm

LED Cube insertion	Manual
Contact OPTIKA fo	r other custom LED Fluorescence Cube options
	Emission: 615-645 nm
ANDER LED Cabe (Optional)	Dichroic: 610 nm;
AMBER LED Cube (Optional)	Excitation: 582 - 603 nm;
	LED Emission: 590 nm.
	Emission: 780LP nm
FAR RED LED Cube (Optional) **	Dichroic: 770 nm;
FAR RED LED Cube (Ontional) **	Excitation: 720 - 760 nm;
	LED Emission: 740 nm.
	Emission: 690-750 nm
DEEP RED LED Cube (Optional) **	Dichroic: 685 nm;
DEED DED 150 C by (0 11 1 11) **	Excitation: 623 - 678 nm;
	LED Emission: 660 nm.
	Emission: 665-715 nm
RED2 LED Cube (Optional) **	Dichroic: 655 nm;
PED2 50 C /O	Excitation: 595 - 645 nm;
	LED Emission: 623 nm.
	Emission: 665LP nm
RED1 LED Cube (Optional) **	Dichroic: 660 nm;
	Excitation: 590 - 650 nm;
	LED Emission: 623 nm.

^{**} If the use of a camera is needed, please order it by specifying with "AR GLASS" in order to observe above 650nm

100/240 Vac, 50/60 Hz

12 Vdc 1.5 A

Fluorescence Light Source	Light source	LED Fluorescence Cube
	Light source power (W)	3,5
	LED wavelength	see LED Fluorescence Cube specs
	Lifetime (hours)	> 65,000
	Brightness control	Yes
Fluorescence Power	Туре	External
Supply	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)

Input voltage

Output voltage