



Stereomicroscope, with pillar stand, 20x-40x, with rechargeable battery

Observation Method - Transmitted Light	Brightfield	Yes
Observation Method - Incident Light	Brightfield	Yes
Head	Type	Binocular
	Construction material	Aluminum & Plastic molds / Aluminum gears
	Inclination	45°
	Interpupillary distance (mm)	53-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	30.5
Eyepieces	Field number (mm)	20
	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	Rubber cup	Yes
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	Achromatic
	Working distance (mm)	57
	Standard magnifications	20x, 40x (rotating turret)
	Objective resolution	19 lp/mm @ 2x lens 24 lp/mm @ 4x lens
Focusing System	Type	Coarse
	Coarse total travel (mm)	37
	Adjustable tension	Yes
Stand	Type	Pillar
	Pillar diameter (mm)	14
	Frosted diffusion plate for transmitted ill.	Yes, diameter 60 mm
	Black/white contrast plate for incident ill.	Yes, diameter 60 mm
	Specimen clips	Yes
Transmitted Illumination	Type	LED
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000

	Temperature (K)	6,300
	Max. required power (W)	1,5
Incident Illumination	Type	LED
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5
Power Supply for Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Use with batteries	Yes, not supplied
	Battery type	Ni-MH (3x, AA size), 1.2V, 1300mAh
	Working time of batteries (hours)	up to 8
Accessories Included	Charging time of batteries (hours)	8
	Dust cover	Yes
	Tension adjustment tool	Yes
Additional Information	User Manual	Digital version (downloadable)
	Maximum sample height (mm):	75
Product Dimensions	Total height (mm)	288
	Base height (mm)	45
	Base width (mm)	183
	Base depth (mm)	205
Product Weight	(kg)	1,8