



*Digital stereomicroscope with 4 MP USB/LAN/WiFi camera, precision fixed arm, 10x - 20x - 40x, touch panel, with rechargeable battery*

<b>Observation Method - Transmitted Light</b>	Brightfield	Yes
<b>Observation Method - Incident Light</b>	Brightfield	Yes
<b>Head</b>	Type	Binocular
	Construction material	Aluminum & Plastic molds / Aluminum gears
	Inclination	45°
	Interpupillary distance (mm)	53-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	30.5
<b>Eyepieces</b>	Field number (mm)	20
	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	Rubber cup	Yes
<b>Objective</b>	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	Achromatic
	Working distance (mm)	60
	Standard magnifications	10x, 20x, 40x (rotating turret)
	Objective resolution	7 lp/mm @ 1x lens 19 lp/mm @ 2x lens 24 lp/mm @ 4x lens
<b>Focusing System</b>	Type	Coarse
	Coarse total travel (mm)	41
	Adjustable tension	Yes
<b>Stand</b>	Type	Precision fixed arm
	Handle	Yes
<b>Stage</b>	Frosted diffusion plate for transmitted ill.	Yes, diameter 60 mm
	Black/white contrast plate for incident ill.	Yes, diameter 60 mm
	Specimen clips	Yes

<b>Transmitted Illumination</b>	Type	LED
	Light source power (W)	1
	Brightness control	Touch Panel
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5
<b>Incident Illumination</b>	Type	LED
	Light source power (W)	1
	Brightness control	Touch Panel
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5
<b>Power Supply for Illumination</b>	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 2,5A
	LED indicator	Yes
	Use with batteries	Yes, not supplied
	Battery type	Ni-MH (3x, AA size), 1.2V, 1300mAh
	Working time of batteries (hours)	up to 8
Charging time of batteries (hours)	8	
<b>Accessories Included</b>	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	USB cable (m)	1,8
	Calibration slide	Yes
<b>Additional Information</b>	Maximum sample height (mm)	35
<b>Product Dimensions</b>	Total height (mm)	288
	Base height (mm)	45
	Base width (mm)	183
	Base depth (mm)	205
<b>Product Weight</b>	(kg)	2,5
<b>Digital Head</b>	Resolution (MP)	4
	Sensor type	CMOS
	Sensor size	1/1.8"
	Sensor aspect ratio	16/9
	Full image size	2688x1512
	Pixel size (µm)	2.9x2.9
	S/N ratio (dB)	43
	Dynamic range (dB)	61
	Sensitivity (V/lux*s @550nm)	No
	Exposure time (s)	0,6 - 1/1000
	USB type	Mini USB
	System requirements	Win 7 / Win 8 / Win 10 (32/64 bit) / Win 11
	Software	ProView
	Software	LiteView
Software	Optika MobileView	
<b>USB</b>	PC Camera resolution (MP)	4
	USB standard	Mini USB
	Frame rate full resolution (fps)	30@2688*1512

<b>WiFi</b>	WiFi resolution (MP)	4
	WiFi Frame rate full resolution (fps)	30@2688*1512
	WiFi Speed	802.11ac 150Mbps
	WiFi Signal	From the camera
	WiFi Antenna	Yes
	WiFi Signal ready	About 10 seconds after turning on
	WiFi mode	AP / STA
	Max Users connected to a single camera	3
	Max number of cameras in a room (AP mode)	6
	Max number of cameras in a room (STA mode)	Not fixed. 9 cameras must be connected to a router

<b>Ethernet</b>	Ethernet resolution (MP)	4
	Ethernet type	802.3ab